

Synchronous Regulator with Bypass Mode, TINYBOOST[®], 2.5 MHz, 1500 mA

FAN48630

Description

The FAN48630 allows systems to take advantage of new battery chemistries that can supply significant energy when the battery voltage is lower than the required voltage for system power ICs. By combining built-in power transistors, synchronous rectification, and low supply current; this IC provides a compact solution for systems using advanced Li-Ion battery chemistries.

The FAN48630 is a boost regulator designed to provide a minimum output voltage from a single-cell Li-Ion battery, even when the battery voltage is below system minimum. Output voltage regulation is guaranteed to a maximum load current of 1500 mA. Quiescent current in Shutdown Mode is less than 3 μ A, which maximizes battery life. The regulator transitions smoothly between Bypass and normal Boost Mode. The device can be forced into Bypass Mode to reduce quiescent current.

The FAN48630 is available in a 16-bump, 0.4 mm pitch, Wafer-Level Chip-Scale Package (WLCSP).

Features

- Few External Components: 0.47 μ H Inductor and 0603 Case Size Input and Output Capacitors
- Input Voltage Range: 2.35 V to 5.5 V
- Fixed Output Voltage Options: 3.0 V to 5.0 V
- Maximum Continuous Load Current: 1500 mA at V_{IN} of 2.6 V Boosting V_{OUT} to 3.5 V
- Up to 96% Efficient
- True Bypass Operation when $V_{IN} > V_{OUT_TARGET}$
- Internal Synchronous Rectifier
- Soft-Start with True Load Disconnect
- Forced Bypass Mode
- V_{SEL} Control to Optimize Target V_{OUT}
- Short-Circuit Protection
- Low Operating Quiescent Current
- 16-Bump, 0.4 mm Pitch WLCSP
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant

Applications

- Boost for Low-Voltage Li-ion Batteries, Brownout Prevention, Boosted Audio, USB OTG, and LTE / 3G RF Power
- Cell Phones, Smart Phones, Portable Instruments




ON Semiconductor[®]

www.onsemi.com



WLCSP16 1.78x1.78x0.586
CASE 567SY

MARKING DIAGRAM



- 12 = Alphanumeric Device Marking
- KK = Lot Rune Code
- X = Alphabetical Year Code
- Y = 2-weeks Date Code
- Z = Assembly Plant Code

ORDERING INFORMATION

See detailed ordering and shipping information on page 2 of this data sheet.




Figure 1. Typical Application

FAN48630

Table 1. ORDERING INFORMATION

| Part Number | Output Voltage (Note 1) V_{SELO}/V_{SEL1} | Soft - Start | Forced Bypass | Operating Temperature | Package | Shipping† | Top Marking |
|-----------------------------|---|-----------------|------------------|--------------------------|---|-------------|----------------|
| FAN48630UC315X | 3.15 / 3.33 | FAST | Low I_Q | -40 to 85°C | 16-Ball, 4x4 Array, 0.4mm Pitch, 250um Ball, Wafer-Level Chip-Scale Package (WLCSP) | Tape & Reel | J5 |
| FAN48630BUC315X (Note 2) | 3.15 / 3.33 | FAST | Low I_Q | | | | J5 |
| FAN48630UC33X | 3.30 / 3.49 | FAST | Low I_Q | | | | JX |
| FAN48630BUC33X (Note 2) | 3.30 / 3.49 | FAST | Low I_Q | | | | JX |
| FAN48630BUC34X (Note 2) | 3.20 / 3.40 | FAST | Low I_Q | | | | JR |
| FAN48630UC35X | 3.50 / 3.70 | FAST | Low I_Q | | | | J6 |
| FAN48630UC37AX | 3.70 / 3.77 | FAST | Low I_Q | | | | JT |
| FAN48630UC45X | 4.50 / 4.76 | SLOW | OCP On | | | | J7 |
| FAN48630UC50X | 5.00 / 5.29 | SLOW | OCP On | | | | J8 |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

1. Other output voltages are available on request. Please contact a ON Semiconductor representative.
2. The FAN48630BUC315X, FAN48630BUC33X and FAN48630BUC34X include backside lamination.

TYPICAL APPLICATION




Figure 2. Block Diagram

FAN48630

Table 2. RECOMMENDED COMPONENTS

| Component | Description | Vendor | Parameter | Typ. | Unit |
|------------------|--------------------------------------|--|----------------|------|------------|
| L ₁ | 0.47 μ H, 30% | Toko: DFE201612C DFR201612C Cyntec: PIFE20161B | L | 0.47 | μ H |
| | | | DCR (Series R) | 40 | m Ω |
| C _{IN} | 4.7 μ F, 10%, 6.3 V, X5R, 0603 | Murata: GRM188R60J475K TDK: C1608X5R0J475K | C | 4.7 | μ F |
| C _{OUT} | 2 x 10 μ F, 20%, 10 V, X5R, 0603 | TDK: C1608X5R1A106M | C | 20 | μ F |

PIN CONFIGURATION




Figure 3. Top Through View (Bumps Down)




Figure 4. Bottom View

Table 3. PIN DEFINITIONS

| Pin # | Name | Description |
|------------|------|---|
| A1 | EN | <u>Enable</u> . When this pin is HIGH, the circuit is enabled (Note 3). |
| A2 | PG | <u>Power Good</u> . This is an open-drain output. PG is actively pulled LOW if output falls out of regulation due to overload or if thermal protection threshold is exceeded. |
| A3–A4 | VIN | <u>Input Voltage</u> . Connect to Li-Ion battery input power source (Note 3). |
| B1 | VSEL | <u>Output Voltage Select</u> . When boost is running, this pin can be used to select output voltage. |
| B2, C2, D1 | AGND | <u>Analog Ground</u> . This is the signal ground reference for the IC. All voltage levels are measured with respect to this pin. |
| B3–B4 | VOUT | <u>Output Voltage</u> . Place C _{OUT} as close as possible to the device. |
| C1 | BYP | <u>Bypass</u> . This pin can be used to activate Forced Bypass Mode. When this pin is LOW, the bypass switches (Q3 and Q1) are turned on and the IC is otherwise inactive. |
| C3–C4 | SW | <u>Switching Node</u> . Connect to inductor. |
| D2–D4 | PGND | <u>Power Ground</u> . This is the power return for the IC. The C _{OUT} bypass capacitor should be returned with the shortest path possible to these pins. |

3. Do not connect the EN pin to VIN. A logic voltage of 1.8 V should control the EN pin and enable/disable the device.

Table 4. ABSOLUTE MAXIMUM RATINGS

| Symbol | Parameter | Min. | Max. | Unit |
|------------------|--|--------------------------------------|-----------------|------|
| V _{IN} | V _{IN} Input Voltage | -0.3 | 6.5 | V |
| V _{OUT} | V _{OUT} Output Voltage | | 6.0 | V |
| | SW Node | DC | 8.0 | V |
| | | Transient: 10 ns, 3 MHz | 8.0 | V |
| | Other Pins | -0.3 | 6.5 (Note 4) | V |
| ESD | Electrostatic Discharge Protection Level | Human Body Model per JESD22-A114 | 3.0 | kV |
| | | Charged Device Model per JESD22-C101 | 1.5 | kV |
| T _J | Junction Temperature | -40 | +150 | °C |
| T _{STG} | Storage Temperature | -65 | +150 | °C |
| T _L | Lead Soldering Temperature, 10 Seconds | | +260 | °C |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

4. Lesser of 6.5 V or V_{IN} + 0.3 V.

Table 5. RECOMMENDED OPERATING CONDITIONS

| Symbol | Parameter | Min. | Max. | Unit |
|------------------|----------------------|------|------|------|
| V _{IN} | Supply Voltage | 2.35 | 5.5 | V |
| I _{OUT} | Output Current | 0 | 1500 | mA |
| T _A | Ambient Temperature | -40 | +85 | °C |
| T _J | Junction Temperature | -40 | +125 | °C |

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability.

Table 6. THERMAL CHARACTERISTICS

| Symbol | Parameter | Typ. | Unit |
|-----------------|--|------|------|
| θ _{JA} | Junction-to-Ambient Thermal Resistance | 80 | °C/W |
| θ _{JB} | Junction-to-Board Thermal Resistance | 42 | |

Junction-to-ambient thermal resistance is a function of application and board layout. This data is measured with four-layer Fairchild® evaluation boards (1 oz copper on all layers). Special attention must be paid not to exceed junction temperature T_{J(max)} at a given ambient temperature T_A.

Table 7. ELECTRICAL CHARACTERISTICS

Recommended operating conditions, unless otherwise noted, circuit per Figure 1, V_{IN} = 2.35 V to V_{OUT}, T_A = -40°C to 85°C. Typical values are given V_{IN} = 3.0 V and T_A = 25°C.

| Symbol | Parameter | Condition | Min. | Typ. | Max. | Unit |
|-----------------------|---|---|------------------------------|------|---------|----------|
| I _Q | V _{IN} Quiescent Current | Bypass Mode V _{OUT} = 3.5 V, V _{IN} = 4.2 V | | 140 | 190 | μA |
| | | Boost Mode V _{OUT} = 3.5 V, V _{IN} = 2.5 V | | 150 | 250 | μA |
| | | Shutdown: EN = 0, V _{IN} = 3.0 V | | 1.5 | 5.0 | μA |
| | | Forced Bypass Mode V _{OUT} = 3.5 V V _{IN} = 3.5 V | Low I _Q OCP On | | 4 45 | 10 90 |
| I _{LK} | V _{OUT} to V _{IN} Reverse Leakage | V _{OUT} = 5 V, EN = 0 | | 0.2 | 1.0 | μA |
| I _{LK_OUT} | V _{OUT} Leakage Current | V _{OUT} = 0, EN = 0, V _{IN} = 4.2 V | | 0.1 | 1.0 | μA |
| V _{UVLO} | Under-Voltage Lockout | V _{IN} Rising | | 2.20 | 2.35 | V |
| V _{UVLO_HYS} | Under-Voltage Lockout Hysteresis | | | 200 | | mV |
| V _{PG(OL)} | PG Low | I _{PG} = 5 mA | | | 0.4 | V |
| I _{PG_LK} | PG Leakage Current | V _{PG} = 5 V | | | 1 | μA |
| V _{IH} | Logic Level High EN, VSEL, BYP | | 1.2 | | | V |
| V _{IL} | Logic Level Low EN, VSEL, BYP | | | | 0.4 | V |

FAN48630

Table 7. ELECTRICAL CHARACTERISTICS (continued)

Recommended operating conditions, unless otherwise noted, circuit per Figure 1, $V_{IN} = 2.35\text{ V}$ to V_{OUT} , $T_A = -40^\circ\text{C}$ to 85°C . Typical values are given $V_{IN} = 3.0\text{ V}$ and $T_A = 25^\circ\text{C}$.

| Symbol | Parameter | Condition | Min. | Typ. | Max. | Unit |
|--------------------|--|--|------|---------|------|------------------|
| R_{LOW} | Logic Control Pin Pull Downs (LOW Active) | BYP, VSEL, EN | | 300 | | $k\Omega$ |
| I_{PD} | Weak Current Source Pull-Down | BYP, VSEL, EN | | 100 | | nA |
| V_{REG} | Output Voltage Accuracy | Referred to GND, DC, $V_{OUT} - V_{IN} > 100\text{ mV}$ | -2 | | 4 | % |
| V_{TRSP} | Load Transient Response | 500–1250 mA, $V_{IN} = 3.6\text{ V}$, $V_{OUT} = 5.0\text{ V}$ | | ± 4 | | % |
| t_{ON} | On-Time | $V_{IN} = 3.0\text{ V}$, $V_{OUT} = 3.5\text{ V}$, Load $> 1000\text{ mA}$ | | 80 | | ns |
| f_{SW} | Switching Frequency | $V_{IN} = 3.6\text{ V}$, $V_{OUT} = 5.0\text{ V}$, Load = 1000 mA | 2.0 | 2.5 | 3.0 | MHz |
| I_{V_LIM} | Boost Valley Current Limit | $V_{IN} = 2.6\text{ V}$ | 2.6 | 2.9 | 3.1 | A |
| $I_{V_LIM_SS}$ | Boost Valley Current Limit During SS | $V_{IN} = 2.6\text{ V}$ | | 1.6 | | A |
| $V_{MIN_1.5A}$ | Minimum V_{IN} for 1500 mA Load (Short Term) | $V_{OUT} = 5.0\text{ V}$, $T_J < 120^\circ\text{C}$ | | 3.0 | | V |
| | | $V_{OUT} = 4.5\text{ V}$, $T_J < 120^\circ\text{C}$ | | 2.8 | | V |
| | | $V_{OUT} = 3.5\text{ V}$, $T_J < 120^\circ\text{C}$ | | 2.35 | | V |
| | | $V_{OUT} = 3.15\text{ V}$, $T_J < 120^\circ\text{C}$ | | 2.35 | | V |
| I_{SS_PK} | Soft-Start Input Peak Current Limit | LIN1 | Slow | | 350 | mA |
| | | | Fast | | 800 | mA |
| | | LIN2 | Slow | | 700 | mA |
| | | | Fast | | 1600 | mA |
| t_{SS} | Soft-Start EN HIGH to Regulation | Slow, 50 Ω Load | | 1300 | | μs |
| | | Fast, 50 Ω Load | | 600 | | μs |
| V_{OCP} | OCP Comparator Threshold | $V_{IN} = 5.0\text{ V}$, $V_{IN} - V_{OUT}$ | | 200 | | mV |
| V_{OVP} | Output Over-Voltage Protection Threshold | | | 6.0 | 6.3 | V |
| V_{OVP_HYS} | Output Over-Voltage Protection Hysteresis | | | 300 | | mV |
| $R_{DS(ON)N}$ | N-Channel Boost Switch $R_{DS(ON)}$ | $V_{IN} = 3.5\text{ V}$, $V_{OUT} = 3.5\text{ V}$ | | 85 | 120 | $m\Omega$ |
| $R_{DS(ON)P}$ | P-Channel Sync Rectifier $R_{DS(ON)}$ | $V_{IN} = 3.5\text{ V}$, $V_{OUT} = 3.5\text{ V}$ | | 65 | 85 | $m\Omega$ |
| $R_{DS(ON)P_BYP}$ | P-Channel Bypass Switch $R_{DS(ON)}$ | $V_{IN} = 3.5\text{ V}$, $V_{OUT} = 3.5\text{ V}$ | | 65 | 85 | $m\Omega$ |
| T_{120A} | T120 Activation Threshold | | | 120 | | $^\circ\text{C}$ |
| T_{120R} | T120 Release Threshold | | | 100 | | $^\circ\text{C}$ |
| T_{150T} | T150 Threshold | | | 150 | | $^\circ\text{C}$ |
| T_{150H} | T150 Hysteresis | | | 20 | | $^\circ\text{C}$ |
| t_{RST} | FAULT Restart Timer | | | 20 | | ms |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

TYPICAL CHARACTERISTICS

Unless otherwise specified; $V_{IN} = 3.6\text{ V}$, $V_{OUT} = 5\text{ V}$, and $T_A = 25^\circ\text{C}$; circuit and components according to Figure 1.




Figure 5. Efficiency vs. Load Current and Input Voltage, $V_{OUT} = 3.5\text{ V}$




Figure 6. Efficiency vs. Load Current and Temperature, $V_{IN} = 3.0\text{ V}$, $V_{OUT} = 3.5\text{ V}$




Figure 7. Efficiency vs. Load Current and Input Voltage




Figure 8. Efficiency vs. Load Current and Temperature




Figure 9. Efficiency vs. Input Voltage and Output Voltage, 200 mA Load




Figure 10. Efficiency vs. Input Voltage and Output Voltage, 1000 mA Load

TYPICAL CHARACTERISTICS (CONTINUED)

Unless otherwise specified; $V_{IN} = 3.6\text{ V}$, $V_{OUT} = 5\text{ V}$, and $T_A = 25^\circ\text{C}$; circuit and components according to Figure 1.




Figure 11. Output Regulation vs. Load Current and Input Voltage (Normalized to 3.6 V_{IN} , 500 mA Load)




Figure 12. Output Regulation vs. Load Current and Temperature (Normalized to 3.6 V_{IN} , 500 mA Load, $T_A = 25^\circ\text{C}$)




Figure 13. Quiescent Current vs. Input Voltage, Temperature and Mode, $V_{OUT} = 5.0\text{ V}$, Forced Bypass, OCP Active




Figure 14. Quiescent Current vs. Input Voltage, Temperature and Mode, $V_{OUT} = 3.5\text{ V}$, Forced Bypass, Low I_Q




Figure 15. Output Ripple vs. Load Current and Input Voltage




Figure 16. Frequency vs. Load Current and Input Voltage

TYPICAL CHARACTERISTICS (CONTINUED)

Unless otherwise specified; $V_{IN} = 3.6\text{ V}$, $V_{OUT} = 5\text{ V}$, and $T_A = 25^\circ\text{C}$; circuit and components according to Figure 1.




Figure 17. Startup, 50 Ω Load




Figure 18. Startup, 50 Ω Load,
 $V_{IN} = 2.5\text{ V}$, $V_{OUT} = 3.5\text{ V}$




Figure 19. Overload Protection




Figure 20. Load Transient, 100–500 mA,
100 ns Edge




Figure 21. Load Transient, 500–1250 mA,
100 ns Edge




Figure 22. Load Transient, 100–500 mA,
100 ns Edge, $V_{IN} = 3\text{ V}$, $V_{OUT} = 3.5\text{ V}$

TYPICAL CHARACTERISTICS (CONTINUED)

Unless otherwise specified; $V_{IN} = 3.6\text{ V}$, $V_{OUT} = 5\text{ V}$, and $T_A = 25^\circ\text{C}$; circuit and components according to Figure 1.




Figure 23. Transient Overload, 500–1950 mA, 100 ns Edge, $V_{IN} = 3\text{ V}$, $V_{OUT} = 3.5\text{ V}$




Figure 24. Line Transient, 3.0–3.6 V_{IN} , 10 μs Edge, 500 mA Load, $V_{OUT} = 3.15\text{ V}$




Figure 25. Line Transient, 3.0–3.6 V_{IN} , 10 μs Edge, 1,000 mA Load, $V_{OUT} = 3.5\text{ V}$




Figure 26. Line Transient, 3.3–3.9 V_{IN} , 10 μs Edge, 500 mA load, $V_{OUT} = 3.5\text{ V}$




Figure 27. Bypass Entry / Exit, Slow V_{IN} Ramp 1 ms Edge, 500 mA Load, $V_{OUT} = 3.5\text{ V}$, 3.2 – 3.8 V_{IN}




Figure 28. V_{SEL} Step, $V_{IN} = 3\text{ V}$, $V_{OUT} = 3.5\text{ V}$, 500 mA Load

CIRCUIT DESCRIPTION

FAN48630 is a synchronous boost regulator, typically operating at 2.5 MHz in Continuous Conduction Mode (CCM), which occurs at moderate to heavy load current and low V_{IN} voltages. The regulator includes a Bypass Mode that activates when V_{IN} is above the boost regulator’s setpoint.

In anticipation of a heavy load transition, the setpoint can be adjusted upward by fixed amounts with the VSEL pin to reduce the required system headroom during lighter-load operation to save power.

Table 8. OPERATING STATES

| Mode | Description | Invoked When |
|------|----------------------|-----------------------------|
| LIN | Linear Startup | $V_{IN} > V_{OUT}$ |
| SS | Boost Soft-Start | $V_{OUT} < V_{OUT_TARGET}$ |
| BST | Boost Operating Mode | $V_{OUT} = V_{OUT_TARGET}$ |
| BPS | Bypass Mode | $V_{IN} > V_{OUT_TARGET}$ |

Boost Mode

The FAN48630 uses a current-mode modulator to achieve excellent transient response and smooth transitions between CCM and Discontinuous Conduction Mode (DCM) operation. During CCM operation, the device maintains a switching frequency of about 2.5 MHz. In light-load operation (DCM), frequency is reduced to maintain high efficiency.

Table 9. BOOST STARTUP SEQUENCE

| Start State | Entry | Exit | End State | Timeout (µs) |
|-------------|-----------------------------|----------------------------------|-----------|--------------|
| LIN1 | $V_{IN} > UVLO$, EN = 1 | $V_{OUT} > V_{IN}-300\text{ mV}$ | SS | |
| | | | LIN2 | 512 |
| LIN2 | LIN1 Exit | $V_{OUT} > V_{IN}-300\text{ mV}$ | SS | |
| | | TIMEOUT | FAULT | 1024 |
| SS | LIN1 or LIN2 Exit | $V_{OUT} = V_{OUT_TARGET}$ | BST | |
| | | OVERLOAD TIMEOUT | FAULT | 64 |

Shutdown and Startup

If EN is LOW, all bias circuits are off and the regulator is in Shutdown Mode. During shutdown, current flow is prevented from V_{IN} to V_{OUT} , as well as reverse flow from V_{OUT} to V_{IN} . During startup, it is recommended to keep DC current draw below 500 mA.

LIN State

When EN is HIGH and $V_{IN} > UVLO$, the regulator attempts to bring V_{OUT} within 300 mV of V_{IN} using the

internal fixed current source from V_{IN} (Q3). The current is limited to LIN1 set point.

If V_{OUT} reaches $V_{IN}-300\text{ mV}$ during LIN1 Mode, the SS state is initiated. Otherwise, LIN1 times out after 512 µs and LIN2 Mode is entered.

In LIN2 Mode, the current source is incremented to 2 A. If V_{OUT} fails to reach $V_{IN}-300\text{ mV}$ after 1024 µs, a fault condition is declared.

SS State

Upon the successful completion of the LIN state ($V_{OUT} \geq V_{IN}-300\text{ mV}$), the regulator begins switching with boost pulses current limited to 50% of nominal level.

During SS state, V_{OUT} is ramped up by stepping the internal reference. If V_{OUT} fails to reach regulation during the SS ramp sequence for more than 64 µs, a fault condition is declared. If large C_{OUT} is used, the reference is automatically stepped slower to avoid excessive input current draw.

BST State

This is a normal operating state of the regulator.

BPS State

If V_{IN} is above V_{REG} when the SS Mode successfully completes, the device transitions directly to BPS Mode.

FAST and SLOW Soft-Start Options

The fast startup versions feature EN to regulation time of 600 µs. LIN1 and LIN2 phase currents are doubled compared to SLOW options, SS phase is also faster.

Slow startup achieves EN to regulation time of 1300 µs to reduce inrush current.

Table 10. OPERATING STATES

| EN | BYP | Mode | V_{OUT} |
|----|-----|---------------|---|
| 0 | 0 | Shutdown | 0 |
| | 1 | Shutdown | 0 |
| 1 | 0 | Forced Bypass | V_{IN} |
| | 1 | Auto Bypass | V_{OUT_TARGET} or V_{IN} (or $V_{IN} > V_{OUT_TARGET}$) |

FAULT State

The regulator enters the FAULT state under any of the following conditions:

- V_{OUT} fails to achieve the voltage required to advance from LIN state to SS state.
- V_{OUT} fails to achieve the voltage required to advance from SS state to BST state.
- Boost current limit triggers for 2 ms during the BST state.
- V_{DS} protection threshold is exceeded during BPS state.

Once a fault is triggered, the regulator stops switching and presents a high-impedance path between V_{IN} and V_{OUT} . After waiting 20 ms, a restart is attempted.

Power Good

Power good is 0 FAULT, 1 POWER GOOD, open-drain output.

The Power good pin is provided for signaling the system when the regulator has successfully completed soft-start and no faults have occurred. Power good also functions as an early warning flag for high die temperature and overload conditions.

Over-Temperature

The regulator shuts down when the die temperature exceeds 150°C. Restart occurs when the IC has cooled by approximately 20°C.

Bypass Operation

In normal operation, the device automatically transitions from Boost Mode to Bypass Mode, if V_{IN} goes above target V_{OUT} . In Bypass Mode, the device fully enhances both Q1 and Q3 to provide a very low impedance path from V_{IN} to V_{OUT} . Entry to the Bypass Mode is triggered by condition where $V_{IN} > V_{OUT}$ and no switching has occurred during past 5 μ s. To soften the entry to Bypass Mode, Q3 is driven as a linear current source for the first 5 μ s. Bypass Mode exit is triggered when V_{OUT} reaches the target V_{OUT} voltage. During Automatic Bypass Mode, the device is short-circuit protected by voltage comparator tracking the voltage drop from V_{IN} to V_{OUT} ; if the drop exceeds 200 mV, FAULT is declared.

With sufficient load to enforce CCM operation, the Bypass Mode to Boost Mode transition occurs at the target V_{OUT} . The corresponding input voltage at the transition point is:

$$V_{IN} \leq V_{OUT} + I_{LOAD} * (DCR_L + R_{DS(ON)P}) \parallel R_{DS(ON)BYP} \quad (\text{eq. 1})$$

The Bypass Mode entry threshold has 25 mV hysteresis imposed at V_{OUT} to prevent cycling between modes. The transition from Boost Mode to Bypass Mode occurs at the target $V_{OUT}+25$ mV. The corresponding input voltage is:

$$V_{IN} \geq V_{OUT} + 25\text{mV} + I_{LOAD} * (DCR_L + R_{DS(ON)P}) \quad (\text{eq. 2})$$

- PG is released HIGH when the soft-start sequence is successfully completed.
- PG is pulled LOW when PMOS current limit has triggered for 64 μ s OR the die the temperature exceeds 120°C. PG is re-asserted when the device cools below to 100°C.
- Any FAULT condition causes PG to be de-asserted.

Forced Bypass

Entry to Forced Bypass Mode initiates with a current limit on Q3 and then proceeds to a true bypass state. To prevent reverse current to the battery, the device waits until output discharges below V_{IN} before entering Forced Bypass Mode.

For Low-IQ Forced Bypass versions, after the transition is complete, most of the internal circuitry is disabled to minimize quiescent current draw. Short-circuit, UVLO, output OVP and over-temperature protections are inactive in Forced Bypass Mode.

For OCP-On Forced Bypass versions, during Forced Bypass Mode, the device is short-circuit protected by a voltage comparator tracking the voltage drop from V_{IN} to V_{OUT} . If the drop exceeds 200 mV, a FAULT is declared. The over-temperature protection is also active.

VSEL

V_{SEL} can be asserted in anticipation of a positive load transient. Raising V_{SEL} increases V_{OUT_TARGET} by a fixed amount and V_{OUT} is stepped to the corresponding target output voltage in 20 μ s. The functionality can also be utilized to mitigate undershoot during severe line transients, while minimizing V_{OUT} during more benign operating conditions to save power.

EN

Setting the EN pin voltage below 0.4 V disables the part. Placing the voltage above 1.2 V enables the part. Do not connect the EN pin to V_{IN} . A logic voltage of 1.8 V should control the EN pin and enable/disable the device. The EN pin should be pulled HIGH after the V_{IN} voltage has reached a minimum voltage of 2.3 V.

APPLICATION INFORMATION

Output Capacitance (C_{OUT})

Stability

The effective capacitance (C_{EFF}) of small, high-value, ceramic capacitors decreases as bias voltage increases. FAN48630 is guaranteed for stable operation with the minimum value of C_{EFF} (C_{EFF(MIN)}) outlined in Table 11 below.

Table 11. MINIMUM C_{EFF} REQUIRED FOR STABILITY

| Operating Conditions | | C _{EFF(MIN)} (μF) |
|----------------------|------------------------|----------------------------|
| V _{OUT} (V) | I _{LOAD} (mA) | |
| 3.15 | 0 to 1500 | 12 |
| 3.5 | 0 to 1500 | 9 |
| 4.5 and 5 | 0 to 1500 | 6 |

C_{EFF} varies with manufacturer, material, and case size.

Inductor Selection

Recommended nominal inductance value is 0.47 μH.

FAN48630 employs valley-current limiting; peak inductor current can reach 3.8 A for a short duration during overload conditions. Saturation effects cause the inductor current ripple to become higher under high loading as only valley of the inductor current ripple is controlled.

For FAN48630UC315X, FAN48630BUC315X, FAN48630UC33X and FAN48630BUC33X, a 0.33 μH inductor can be used for improved transient performance.

Startup

Input current limiting is in effect during soft-start, which limits the current available to charge C_{OUT} and any additional capacitance on the V_{OUT} line. If the output fails to achieve regulation within the limits described in the Startup section, a FAULT occurs, causing the circuit to shut down then restart after a significant time period. If the total combined output capacitance is very high, the circuit may not start on the first attempt, but eventually achieves regulation if no load is present. If a high-current load and high capacitance are both present during soft-start, the circuit may fail to achieve regulation and continually attempts soft-start, only to have the output capacitance discharged by the load when in a FAULT state.

Output Voltage Ripple

Output voltage ripple is inversely proportional to C_{OUT}. During t_{ON}, when the boost switch is on, all load current is supplied by C_{OUT}. Output ripple is calculated as:

$$V_{\text{RIPPLE(P-P)}} = t_{\text{ON}} * \frac{I_{\text{LOAD}}}{C_{\text{OUT}}} \quad (\text{eq. 3})$$

and

$$t_{\text{ON}} = t_{\text{SW}} * D = t_{\text{SW}} * \left(1 - \frac{V_{\text{IN}}}{V_{\text{OUT}}}\right) \quad (\text{eq. 4})$$

therefore:

$$V_{\text{RIPPLE(P-P)}} = t_{\text{SW}} * \left(1 - \frac{V_{\text{IN}}}{V_{\text{OUT}}}\right) * \frac{I_{\text{LOAD}}}{C_{\text{OUT}}} \quad (\text{eq. 5})$$

and

$$t_{\text{SW}} = \frac{1}{f_{\text{SW}}} \quad (\text{eq. 6})$$

As can be seen from eq. 5, the maximum V_{RIPPLE} occurs when V_{IN} is at minimum and I_{LOAD} is at maximum.

Layout Recommendations

The layout recommendations below highlight various top-copper pours using different colors.

To minimize spikes at V_{OUT}, C_{OUT} must be placed as close as possible to PGND and V_{OUT}, as shown in Figure 29.

For thermal reasons, it is suggested to maximize the pour area for all planes other than SW. Especially the ground pour should be set to fill all available PCB surface area and tied to internal layers with a cluster of thermal vias.




Figure 29. Layout Recommendation

Table 12. PRODUCT-SPECIFIC DIMENSIONS

| D | E | X | Y |
|--------------|--------------|-------|-------|
| 1.780 ±0.030 | 1.780 ±0.030 | 0.290 | 0.290 |

TINYBOOST is registered trademark of Semiconductor Components Industries, LLC (SCILLC) or its subsidiaries in the United States and/or other countries. FAIRCHILD is registered trademark of Semiconductor Components Industries, LLC (SCILLC) or its subsidiaries in the United States and/or other countries.

MECHANICAL CASE OUTLINE






PACKAGE DIMENSIONS

ON Semiconductor®



WLCSP16 1.78x1.78x0.586
CASE 567SY
ISSUE O

DATE 30 NOV 2016



NOTES

- A. NO JEDEC REGISTRATION APPLIES.
- B. DIMENSIONS ARE IN MILLIMETERS.
- C. DIMENSIONS AND TOLERANCE PER ASME Y14.5M, 1994.
- △ D. DATUM C IS DEFINED BY THE SPHERICAL CROWNS OF THE BALLS.
- E. PACKAGE NOMINAL HEIGHT IS 586 ± 39 MICRONS (547-625 MICRONS).
- △ F. FOR DIMENSIONS D, E, X, AND Y SEE PRODUCT DATASHEET.

| | | |
|-------------------------|--------------------------------|--|
| DOCUMENT NUMBER: | 98AON16621G | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION: | WLCSP16 1.78x1.78x0.586 | PAGE 1 OF 1 |

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Email Requests to: orderlit@onsemi.com

ON Semiconductor Website: www.onsemi.com

TECHNICAL SUPPORT

North American Technical Support:
Voice Mail: 1 800-282-9855 Toll Free USA/Canada
Phone: 011 421 33 790 2910

Europe, Middle East and Africa Technical Support:

Phone: 00421 33 790 2910

For additional information, please contact your local Sales Representative

