

	1	2	3	4	5	6	7																																																																																											
A								A																																																																																										
B	<table border="1"> <thead> <tr> <th>POSITION</th> <th>A</th> <th>B</th> <th>C</th> <th>D</th> </tr> </thead> <tbody> <tr> <td>15</td> <td>24.99</td> <td>20.47</td> <td>10.67</td> <td>12.01</td> </tr> <tr> <td>26</td> <td>33.30</td> <td>28.80</td> <td>10.67</td> <td>20.35</td> </tr> <tr> <td>44</td> <td>47.04</td> <td>42.52</td> <td>10.67</td> <td>34.06</td> </tr> <tr> <td>62</td> <td>63.50</td> <td>59.08</td> <td>10.67</td> <td>50.62</td> </tr> <tr> <td>78</td> <td>61.00</td> <td>56.34</td> <td>14.10</td> <td>46.90</td> </tr> </tbody> </table>							POSITION	A	B	C	D	15	24.99	20.47	10.67	12.01	26	33.30	28.80	10.67	20.35	44	47.04	42.52	10.67	34.06	62	63.50	59.08	10.67	50.62	78	61.00	56.34	14.10	46.90	B																																																												
POSITION	A	B	C	D																																																																																														
15	24.99	20.47	10.67	12.01																																																																																														
26	33.30	28.80	10.67	20.35																																																																																														
44	47.04	42.52	10.67	34.06																																																																																														
62	63.50	59.08	10.67	50.62																																																																																														
78	61.00	56.34	14.10	46.90																																																																																														
C	<p style="text-align: center;">Recommended Panel Cut-Out</p>							C																																																																																										
D	<p style="text-align: center;">RoHS compliant Unit: mm</p>							D																																																																																										
E	<table border="1"> <thead> <tr> <th>Scale</th> <th>Free</th> <th>③</th> <th>Update the drawing</th> <th>26.07.2016</th> <th>Jesse</th> <th></th> <th>Date</th> <th>Name</th> <th>Customer-r-No.</th> </tr> </thead> <tbody> <tr> <td>TOLERANCE</td> <td></td> <td>⑤</td> <td>Update the operating temperature</td> <td>27.06.2016</td> <td>Winnie</td> <td>Drawn</td> <td>15.08.2012</td> <td>Lucas</td> <td></td> </tr> <tr> <td>X.</td> <td>±0.15</td> <td>④</td> <td>Correct the PCB dimension for 15 Poles</td> <td>22.03.2016</td> <td>Winnie</td> <td>Approved</td> <td>26.07.2016</td> <td>Jesse</td> <td></td> </tr> <tr> <td>X.X</td> <td>±0.10</td> <td>③</td> <td>Correct the PCB dimension</td> <td>09.03.2016</td> <td>Winnie</td> <td></td> <td></td> <td></td> <td>ASSMANN WSW-No. A-HDX XX A-KG/T</td> </tr> <tr> <td>X.XX</td> <td>±0.05</td> <td>②</td> <td>Update the dimension</td> <td>27.02.2015</td> <td>Winnie</td> <td></td> <td></td> <td></td> <td>Drawing-No. ASS 4897 CO</td> </tr> <tr> <td>DIM</td> <td>TOL</td> <td>①</td> <td>Add the dimension of PCB edge</td> <td>19.02.2014</td> <td>Ray</td> <td></td> <td></td> <td></td> <td>Replace rev06</td> </tr> <tr> <td>X.°</td> <td>±3°</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>Sheet 3/3</td> </tr> <tr> <td>X.X°</td> <td>±1.0°</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Angle</td> <td>TOL</td> <td></td> <td>Modification</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>							Scale	Free	③	Update the drawing	26.07.2016	Jesse		Date	Name	Customer-r-No.	TOLERANCE		⑤	Update the operating temperature	27.06.2016	Winnie	Drawn	15.08.2012	Lucas		X.	±0.15	④	Correct the PCB dimension for 15 Poles	22.03.2016	Winnie	Approved	26.07.2016	Jesse		X.X	±0.10	③	Correct the PCB dimension	09.03.2016	Winnie				ASSMANN WSW-No. A-HDX XX A-KG/T	X.XX	±0.05	②	Update the dimension	27.02.2015	Winnie				Drawing-No. ASS 4897 CO	DIM	TOL	①	Add the dimension of PCB edge	19.02.2014	Ray				Replace rev06	X.°	±3°								Sheet 3/3	X.X°	±1.0°									Angle	TOL		Modification							E
Scale	Free	③	Update the drawing	26.07.2016	Jesse		Date	Name	Customer-r-No.																																																																																									
TOLERANCE		⑤	Update the operating temperature	27.06.2016	Winnie	Drawn	15.08.2012	Lucas																																																																																										
X.	±0.15	④	Correct the PCB dimension for 15 Poles	22.03.2016	Winnie	Approved	26.07.2016	Jesse																																																																																										
X.X	±0.10	③	Correct the PCB dimension	09.03.2016	Winnie				ASSMANN WSW-No. A-HDX XX A-KG/T																																																																																									
X.XX	±0.05	②	Update the dimension	27.02.2015	Winnie				Drawing-No. ASS 4897 CO																																																																																									
DIM	TOL	①	Add the dimension of PCB edge	19.02.2014	Ray				Replace rev06																																																																																									
X.°	±3°								Sheet 3/3																																																																																									
X.X°	±1.0°																																																																																																	
Angle	TOL		Modification																																																																																															
F	<p style="text-align: center;">ASSMANN WSW/ components</p>							F																																																																																										
G	<p style="text-align: center;">ASSMANN WSW/ components</p>							G																																																																																										
H	<p style="text-align: center;">ASSMANN WSW/ components</p>							H																																																																																										
	1	2	3	4	5	6	7																																																																																											