

## Coupling - VS-MP-PPC/CG-PO/FO - 1404321

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Multi-port power and data connection: push/pull power and SC-RJ, for passive PROFINET cabling to robots, including mounting foot.

### Product description

Push/pull power and data coupling; version 14



### Key commercial data

Packing unit	1 pc
Custom tariff number	85366990
Country of origin	Germany

### Technical data

#### Mechanical characteristics

Connection profile	Data/power: SCRJ/5-pos.
Insertion/withdrawal cycles	≥ 500 (Data)
	≤ 100 (Power)
Max. cable diameter	5 mm ... 8 mm (Data cable gland)

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
Degree of protection	IP65

#### Material data

Housing material	Aluminum press-drawn section / die-cast zinc
------------------	--

#### Electrical characteristics

Nominal voltage $U_N$	24 V
Nominal current $I_N$	16 A

# Coupling - VS-MP-PPC/CG-PO/FO - 1404321

## Classifications

### eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27061801
eCl@ss 6.0	27061801
eCl@ss 7.0	27061801

### ETIM

ETIM 3.0	EC000830
ETIM 4.0	EC001134
ETIM 5.0	EC001134

### UNSPSC

UNSPSC 6.01	26121616
UNSPSC 7.0901	26121616
UNSPSC 11	26121604
UNSPSC 12.01	31261501
UNSPSC 13.2	26121616

## Approvals

### Approvals

---

Approvals

EAC

---

Ex Approvals

---

Approvals submitted

---


Approval details

EAC
-----

## Drawings

## Coupling - VS-MP-PPC/CG-PO/FO - 1404321

Drilling diagram



Dimensioned drawing

