

Passive module - UM 45-FLK50/S5/A-S115 - 2965059

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



VARIOFACE COMPACT LINE interface module, for analog I/Os of the SIMATIC® S5-135U with SIMATIC®-specific marking

The illustration shows version UM 45-FLK50/PLC



Key commercial data

Packing unit	1 PCE
Weight per Piece (excluding packing)	139.4 GRM
Custom tariff number	85369010
Country of origin	Germany

Technical data

Dimensions

Width	126 mm
Height	45 mm
Depth	50 mm

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

General

Nominal voltage U_N	25 V AC
	50 V DC
Max. current carrying capacity per branch	1 A
Number of positions	50
Test voltage	500 V AC (50 Hz, 1 min.)

Passive module - UM 45-FLK50/S5/A-S115 - 2965059

Technical data

General

Mounting position	any
Standards/regulations	IEC 60664
	DIN VDE 0110
	DIN VDE 0160 (in parts)
Pollution degree	2
Surge voltage category	II

Connection data for connection 1

Conductor cross section solid min.	0.14 mm ²
Conductor cross section solid max.	1.5 mm ²
Conductor cross section stranded min.	0.14 mm ²
Conductor cross section stranded max.	1.5 mm ²
Conductor cross section AWG/kcmil min.	26
Conductor cross section AWG/kcmil max	14
Stripping length	6 mm
Screw thread	M3

Classifications

eCl@ss

eCl@ss 4.0	27250313
eCl@ss 4.1	27250313
eCl@ss 5.0	27250313
eCl@ss 5.1	27250313
eCl@ss 6.0	27371601
eCl@ss 7.0	27371601

ETIM

ETIM 2.0	EC001437
ETIM 3.0	EC001437
ETIM 4.0	EC001437
ETIM 5.0	EC001437

UNSPSC

UNSPSC 6.01	30211824
UNSPSC 7.0901	39121421
UNSPSC 11	39121421
UNSPSC 12.01	39121421

Passive module - UM 45-FLK50/S5/A-S115 - 2965059

Classifications

UNSPSC

UNSPSC 13.2	39121421
-------------	----------

Approvals

Approvals


Approvals

GOST

Ex Approvals

Approvals submitted

Approval details

GOST 
--

Drawings

Passive module - UM 45-FLK50/S5/A-S115 - 2965059

Circuit diagram

